

LITHO GRADIENT comfortBACK ECO

<p>CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR</p> <p>PILE MATERIAL COUCHE D'USURE POLMATERIAL POOLMATERIAAL</p> <p>SECONDARY BACKING DOSSIER RÜCKENAUSSTATTUNG RUG</p> <p>TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT</p> <p>PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT</p> <p>PILE ABOVE BACKING POIDS DE VELOURS UTILE POLNUTZSCHICHTGEWICHT NUTTIG POOLGEWICHT</p> <p>TOTAL HEIGHT EPAISSEUR TOTALE GESAMTDICKE TOTALE DIKTE</p> <p>PILE HEIGHT EPAISSEUR DU VELOURS POLDICKE POOLHOOGTE</p> <p>PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTE POOLDICHTHEID</p> <p>TUFT DENSITY NOMBRE DE TOUFFES NOPPENZAHL AANTAL PUNTEN</p> <p>CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE</p> <p>CASTOR CHAIR SUITABILITY EMPLOI CHAISE À ROULETTES STUHLROLLENEIGNUNG ROLSTOELGESCHIKTHEID</p> <p>CRADLE TO CRADLE CERTIFIED™</p>	<p>Tufted 1/12" Loop Tufté 1/12" Bouclé Getuftet 1/12" Schlinge Getuft 1/12" Luspool</p> <p>100% ECONYL® yarn 100% regenerated solution dyed nylon</p> <p>comfortBack^{eco}: shock absorbing and noise reducing carpet tile backing enhanced with a fully recyclable polyolefin based layer made from minimum 60% post-industrial recycled content</p> <p>Ca. 3.800 g/m²</p> <p>Ca. 660 g/m²</p> <p>Ca. 450 g/m²</p> <p>Ca. 9,4 mm</p> <p>Ca. 3,5 mm</p> <p>Ca. 0,129 g/cm³</p> <p>Ca. 220.000 /m²</p> <p>EN 1307 33- LC2</p> <p>ISO 4918 A : continuous use</p> <p>Gold level according to version 4.0. 10, 12, 208, 398, 501, 518, 626, 853, 901, 904, 911, 932, 983</p> <p>Silver level according to version 4.0. 389, 659, 672</p>	<p>FIRE RESISTANCE COMPOSITE AU FEU BRENNVERHALTEN BRANDGEDRAG</p> <p>FASTNESS TO LIGHT SOLIDITÉ À LA LUMIÈRE LICHTECHTHEIT LICHTECHTHEID</p> <p>RUBBING FASTNESS SOLIDITÉ AU FROTTEMENT REIBECHTHEIT WRIJFECHTHEID</p> <p>COLOUR FASTNESS TO WATER SOLIDITÉ À L'EAU WASSERECHTHEIT WATERECHTHEID</p> <p>THERMAL RESISTANCE RÉSISTANCE THERMIQUE WÄRMEDURCHLABWIDERSTAND WARMTEDOORLAATWEERSTAND</p> <p>IMPACT NOISE RATING ISOLATION PHONIQUE TRITTSCHALLVERBESSERUNGSMAB GELUIDSISOLATIE</p> <p>SOUND ABSORPTION ABSORPTION PHONIQUE SCHALLABSORPTIONSGRAD GELUIDSABSORPTIE</p> <p>PERMANENT ANTISTATIC ANTISTATIQUE PERMANENT PERMANENT ANTISTATISCH PERMANENT ANTISTATISCH</p> <p>TRANSVERSAL RESISTANCE RÉSISTANCE TRANSVERSALE DURCHGANGSWIDERSTAND DOORGANGSWEERSTAND</p> <p>SIZE & PACKING DIMENSION & EMBALLAGE ABMESSUNG & VERPACKUNG AFMETINGEN & VERPAKKING</p> <p>NUMBER OF COLOURS NOMBRE DE COLORIS ANZAHL DER FARBEN AANTAL KLEUREN</p> <p>DIMENSIONAL STABILITY STABILITÉ DIMENSIONNELLE DIMENSIONSTABILITÄT DIMENSIONELE STABILITEIT</p> <p>GUT-NR</p> <p>LEED®</p> <p>DGNB</p>	<p>EN 13501-1 B_{s1}-s1</p> <p>ISO 105-B02 ≥ 7</p> <p>EN ISO 105-X12 ≥ 4</p> <p>EN ISO 105-E01 ≥ 4</p> <p>ISO 8302 ca. 0.104 m²/K/W</p> <p>ISO 10140 ΔL_w: ca 30 dB</p> <p>ISO 354 α_w: 0,30</p> <p>ISO 6356 ≤ 2 kV</p> <p>ISO/DIS 10965 ≤ 1 x 10¹¹ Ohm</p> <p>50 cm x 50 cm box: 4 m² pallet: 20 boxes</p> <p>16</p> <p>EN 986 max. 0,2 %</p> <p>7D7DBFDB</p> <p>Product contributes toward satisfying Credits under LEED®.*</p> <p>modulyss is member of DGNB, the German Sustainable Building Council.</p>
---	---	--	--

* For more information, see the modulyss sustainable datasheets. - Remark: Products are not reviewed under LEED®, LEED® credit requirements cover the performance of materials in aggregate, not the performance of individual products of brands. The LEED® green building certification program is the nationally accepted benchmark for the design, construction, and operation of green buildings. For more information on LEED®, visit www.usgbc.org/contact.

